

current width. It will block the sunrays in hot period and allow it to enter in cold period. Diagonal fins will completely block the sun rays in the cold period when the sun is crucially required it cloud perform well in intermediate period such as in September. Moreover, diagonal fins block the view to outside while egg-crate will allow for kind of connections to outside. Modified egg-crate could go well with current situation, fewer modifications, as vertical slats of small width can be easily installed on the window sills and horizontal part can be fixed on vertical slats. Further studies are required to study the effect of shading devices on daylight, visual environment and view out.

References

- [1] Datta, G., Effect of fixed horizontal louver shading devices on thermal performance of building by TRNSYS simulation. *Renewable Energy* 23, 2001, p. 497–507.
- [2] Palmero-Marrero, A.I. and A.C. Oliveira, effect of louver shading devices on building energy requirements *Applied Energy* 87, 2010, p. 2040-2049.
- [3] Bessoudo, M., et al., Indoor thermal environmental conditions near glazed facades with shading devices e Part I: Experiments and building thermal model. *Building and Environment* 45, 2010, p. 2506-2516.
- [4] Tzempelikos, A., et al. the impact of shading devices on the thermal comfort conditions in perimeter zones with glass facades. in 2nd PALENC conference and 28th AIVC conference on building low energy cooling and advanced ventilation technologies in the 21st century. 2007, Crete Island, Greece, P 1072-1077
- [5] Tzempelikos, A., et al., Indoor thermal environmental conditions near glazed facades with shading devices e Part II: Experiments and building thermal model. *Building and Environment* 45, 2010. p. 2517-2525.
- [6] Freewan, A.A., L. Shao, and S. Riffat, Interactions between louvers and ceiling geometry for maximum daylighting performance. *Renewable Energy* 34, 2009, p. 223-232.
- [7] Tzempelikos, A. and A.K. Athienitis, The impact of shading design and control on building cooling and lighting demand. *Solar Energy* 81, 2007, p. 369-382.
- [8] Chou, C.-P., The Performance of Daylighting with Shading Device in Architecture Design. *Tamkang Journal of Science and Engineering* 7, 2004, p. 205-212.
- [9] Dubois, M.C., Shading devices and daylight quality: an evaluation based on simple performance indicators. *Lighting Research and Technology* 35, 2003, p. 61-76.
- [10] Lee, E.S., D.L. DiBartolomeo, and S.E. Selkowitz, Thermal and daylighting performance of an automated venetian blind and lighting system in a full-scale private office. *Energy and Buildings* 29(1), 1998, p. 47-63.
- [11] Wong and I. Agustinus Djoko, Effect of external shading devices on daylighting penetration in residential buildings. *Lighting Research and Technology* 36, 2004, p. 317-333.
- [12] Sutter, Y., D. Dumortier, and M. Fontoynt, The use of shading systems in VDU task offices: A pilot study. *Energy and Buildings* 38, 2006, p. 780-789.
- [13] Yoo, S.-H. and E.-T. Lee, Efficiency characteristic of building integrated photovoltaics as a shading device. *Building and Environment* 37, 2002, P. 615-623.